

<b>REQUEST FOR QUOTATION</b> <i>(THIS IS NOT AN ORDER)</i>		THIS RFQ _ IS x IS NOT A SMALL BUSINESS SET-ASIDE			Page 1 of 3		
1. REQUEST NO. <b>19U/Z8020Q0022</b>	2. DATE ISSUED <b>09/08/2020</b>	3. REQUISITION/PURCHASE REQUEST NO. <b>PR9419505</b>	4. CERT. FOR NAT. DEF. UNDER BDSA REG. 2 AND/OR DMS REG. 1	RATING			
5a. ISSUED BY  <b>American Embassy Tashkent Embassy of the United States of America in Tashkent 3, Mayqorghon Street, 5th block, Yunusobod District Tashkent, Uzbekistan 100093</b>			6. DELIVER BY (Date)  <b>10 days after notice to proceed</b>				
5b. FOR INFORMATION CALL (NO COLLECT CALLS)			7. DELIVERY				
NAME  <b>Irina Mezentseva</b>		TELEPHONE NUMBER <b>+99878 120-54-50</b>		_ FOB DESTINATION <input checked="" type="checkbox"/> OTHER (See General Conditions/Requirements)			
8. TO:			9. DESTINATION				
a. NAME		b. COMPANY		a. NAME OF CONSIGNEE Per <b>American Embassy Tashkent, Uzbekistan</b>			
c. STREET ADDRESS			b. STREET ADDRESS <b>3, Mayqorghon Street, 5th block, Yunusobod District</b>				
d. CITY			c. CITY <b>Tashkent</b>				
e. STATE		f. ZIP CODE		d. STATE <b>Uzbekistan</b>		e. ZIP CODE <b>100093</b>	
10. PLEASE FURNISH QUOTATIONS TO THE ISSUING OFFICE IN BLOCK 5A ON OR BEFORE CLOSE OF BUSINESS (Date) <b>09/23/2020 12:00 Tashkent time</b>			<b>IMPORTANT:</b> This is a request for information, and quotations furnished are not offers. If you are unable to quote, please so indicate on this form and return it to the address in Block 5A. This request does not commit the Government to pay any costs incurred in the preparation of the submission of this quotation or to contract for supplies or services. Supplies are of domestic origin unless otherwise indicated by quoter. Any representations and/or certifications attached to this Request for Quotations must be completed by the quoter.				
<b>11. SCHEDULE (Include applicable Federal, State and local taxes)</b>							
ITEM NO. (a)	SUPPLIES/SERVICES (b)	QUANTITY (c)	UNIT (d)	UNIT PRICE (e)	AMOUNT (f)		
1.	<b>Electric low lift pallet truck with foldable driver's platform per Specifications in 11. Schedule</b>						
12. DISCOUNT FOR PROMPT PAYMENT		a. 10 CALENDAR DAYS (%)		b. 20 CALENDAR DAYS (%)		c. 30 CALENDAR DAYS (%)	
		d. CALENDAR DAYS		NUMBER		PERCENTAGE	
NOTE: Additional provisions and representations [ ] are [ ] are not attached.							
13. NAME AND ADDRESS OF QUOTER			14. SIGNATURE OF PERSON AUTHORIZED TO SIGN QUOTATION		15. DATE OF QUOTATION		
a. NAME OF QUOTER			16. SIGNER		b. TELEPHONE		
STREET ADDRESS							
c. COUNTY			a. NAME (Type or print)		AREA CODE		
d. CITY	e. STATE	f. ZIP CODE	c. TITLE (Type or print)		NUMBER		

**11. SCHEDULE**  
*(Include applicable Federal, State and local taxes)*

ITEM NO. (a)	SUPPLIES/SERVICES (b)	Q-TY (c)	UNIT (d)	UNIT PRICE (e)	AMOUNT (f)																																																																																																																																																																																								
1.	<p><b>Electric low lift pallet truck with foldable driver's platform</b></p> <p>Specification:</p> <table border="1" data-bbox="180 296 1065 1856"> <tr><td colspan="3">Drive</td><td>24V Electric</td></tr> <tr><td colspan="3">Operator type</td><td>Pedestrian/Stand-On</td></tr> <tr><td>Rated capacity/rated load</td><td>Q (kg)</td><td></td><td>2000</td></tr> <tr><td>Load centre distance</td><td>c (mm)</td><td></td><td>600</td></tr> <tr><td>Load distance</td><td>x (mm)</td><td></td><td>1005</td></tr> <tr><td>Wheelbase</td><td>y (mm)</td><td></td><td>1356</td></tr> <tr><td>Service weight incl. battery (see 6.5)</td><td>kg</td><td></td><td>515</td></tr> <tr><td>Axle loading, laden front/rear</td><td>kg</td><td></td><td>855/1660</td></tr> <tr><td>Axle loading, unladen front/rear</td><td>kg</td><td></td><td>407/108</td></tr> <tr><td colspan="3">Tyres</td><td>Polyurethane</td></tr> <tr><td colspan="3">Tyre size, front</td><td>Ø 230x82</td></tr> <tr><td colspan="3">Tyre size, rear</td><td>Ø 85x110/Ø 85x70</td></tr> <tr><td colspan="3">Additional wheels (dimensions)</td><td>Ø 100x40</td></tr> <tr><td colspan="3">Wheels, number front/rear (x = driven wheels)</td><td>1x +2/2 or 4</td></tr> <tr><td>Tread, front</td><td>b10 (mm)</td><td></td><td>490</td></tr> <tr><td>Tread, rear</td><td>b11 (mm)</td><td></td><td>385</td></tr> <tr><td>Lift</td><td>h3 (mm)</td><td></td><td>130</td></tr> <tr><td>Lift height</td><td>h3 + h13 (mm)</td><td></td><td>215</td></tr> <tr><td>Stand height</td><td>h7 (mm)</td><td></td><td>160</td></tr> <tr><td>Height tiller in driving position min./max.</td><td>h14 (mm)</td><td></td><td>796/1219</td></tr> <tr><td>Height tiller in driving position min./max. (w/ platform)</td><td>(mm)</td><td></td><td>1066/1290</td></tr> <tr><td>Height, lowered</td><td>h13 (mm)</td><td></td><td>85</td></tr> <tr><td>Overall length</td><td>l1 (mm)</td><td></td><td>1692</td></tr> <tr><td>Length to face of forks</td><td>l2 (mm)</td><td></td><td>532</td></tr> <tr><td>Overall width</td><td>b1 (mm)</td><td></td><td>710</td></tr> <tr><td>Fork dimensions</td><td>s • e • l (mm)</td><td></td><td>55x175x1150</td></tr> <tr><td>Distance between fork-arms</td><td>b5 (mm)</td><td></td><td>560</td></tr> <tr><td>Ground clearance, centre of wheelbase</td><td>m2 (mm)</td><td></td><td>28</td></tr> <tr><td>Aisle width for pallets 1000 x 1200 sideways</td><td>Ast (mm)</td><td></td><td>1731</td></tr> <tr><td>Aisle width for pallets 800 x 1200 lengthways</td><td>Ast (mm)</td><td></td><td>1931</td></tr> <tr><td>Turning radius</td><td>Wa (mm)</td><td></td><td>1536</td></tr> <tr><td>Travel speed, laden/unladen</td><td>km/h</td><td></td><td>6/6</td></tr> <tr><td>Lift speed, laden/unladen</td><td>m/s</td><td></td><td>0.04/0.05</td></tr> <tr><td>Lowering speed, laden/unladen</td><td>%</td><td></td><td>0.05/0.05</td></tr> <tr><td>Max. gradeability, laden/unladen *1</td><td></td><td></td><td>8/20</td></tr> <tr><td>Service brake</td><td></td><td></td><td>Electric</td></tr> <tr><td>Drive motor rating S2 60 min</td><td>kW</td><td></td><td>1.2</td></tr> <tr><td>Lift motor rating at S3 15 %</td><td>kW</td><td></td><td>1.2</td></tr> <tr><td>Battery acc. to DIN 43531/35/36 A, B, C, no</td><td></td><td></td><td>Option</td></tr> <tr><td>Battery voltage/nominal capacity</td><td>Ah/5hr</td><td></td><td>24V/150 (250Ah)</td></tr> <tr><td>Battery weight</td><td>kg</td><td></td><td>151</td></tr> <tr><td>Energy consumption acc. to VDI cycle</td><td>kWh/h</td><td></td><td>-</td></tr> <tr><td>- Battery type</td><td></td><td></td><td>Traction battery</td></tr> <tr><td>Type of drive unit</td><td></td><td></td><td>AC</td></tr> <tr><td>Steering design</td><td></td><td></td><td>Mechanical</td></tr> <tr><td>Sound pressure level at the driver's seat acc. to EN 12053</td><td>dB(A)</td><td></td><td>63</td></tr> </table>	Drive			24V Electric	Operator type			Pedestrian/Stand-On	Rated capacity/rated load	Q (kg)		2000	Load centre distance	c (mm)		600	Load distance	x (mm)		1005	Wheelbase	y (mm)		1356	Service weight incl. battery (see 6.5)	kg		515	Axle loading, laden front/rear	kg		855/1660	Axle loading, unladen front/rear	kg		407/108	Tyres			Polyurethane	Tyre size, front			Ø 230x82	Tyre size, rear			Ø 85x110/Ø 85x70	Additional wheels (dimensions)			Ø 100x40	Wheels, number front/rear (x = driven wheels)			1x +2/2 or 4	Tread, front	b10 (mm)		490	Tread, rear	b11 (mm)		385	Lift	h3 (mm)		130	Lift height	h3 + h13 (mm)		215	Stand height	h7 (mm)		160	Height tiller in driving position min./max.	h14 (mm)		796/1219	Height tiller in driving position min./max. (w/ platform)	(mm)		1066/1290	Height, lowered	h13 (mm)		85	Overall length	l1 (mm)		1692	Length to face of forks	l2 (mm)		532	Overall width	b1 (mm)		710	Fork dimensions	s • e • l (mm)		55x175x1150	Distance between fork-arms	b5 (mm)		560	Ground clearance, centre of wheelbase	m2 (mm)		28	Aisle width for pallets 1000 x 1200 sideways	Ast (mm)		1731	Aisle width for pallets 800 x 1200 lengthways	Ast (mm)		1931	Turning radius	Wa (mm)		1536	Travel speed, laden/unladen	km/h		6/6	Lift speed, laden/unladen	m/s		0.04/0.05	Lowering speed, laden/unladen	%		0.05/0.05	Max. gradeability, laden/unladen *1			8/20	Service brake			Electric	Drive motor rating S2 60 min	kW		1.2	Lift motor rating at S3 15 %	kW		1.2	Battery acc. to DIN 43531/35/36 A, B, C, no			Option	Battery voltage/nominal capacity	Ah/5hr		24V/150 (250Ah)	Battery weight	kg		151	Energy consumption acc. to VDI cycle	kWh/h		-	- Battery type			Traction battery	Type of drive unit			AC	Steering design			Mechanical	Sound pressure level at the driver's seat acc. to EN 12053	dB(A)		63	1	Each		
Drive			24V Electric																																																																																																																																																																																										
Operator type			Pedestrian/Stand-On																																																																																																																																																																																										
Rated capacity/rated load	Q (kg)		2000																																																																																																																																																																																										
Load centre distance	c (mm)		600																																																																																																																																																																																										
Load distance	x (mm)		1005																																																																																																																																																																																										
Wheelbase	y (mm)		1356																																																																																																																																																																																										
Service weight incl. battery (see 6.5)	kg		515																																																																																																																																																																																										
Axle loading, laden front/rear	kg		855/1660																																																																																																																																																																																										
Axle loading, unladen front/rear	kg		407/108																																																																																																																																																																																										
Tyres			Polyurethane																																																																																																																																																																																										
Tyre size, front			Ø 230x82																																																																																																																																																																																										
Tyre size, rear			Ø 85x110/Ø 85x70																																																																																																																																																																																										
Additional wheels (dimensions)			Ø 100x40																																																																																																																																																																																										
Wheels, number front/rear (x = driven wheels)			1x +2/2 or 4																																																																																																																																																																																										
Tread, front	b10 (mm)		490																																																																																																																																																																																										
Tread, rear	b11 (mm)		385																																																																																																																																																																																										
Lift	h3 (mm)		130																																																																																																																																																																																										
Lift height	h3 + h13 (mm)		215																																																																																																																																																																																										
Stand height	h7 (mm)		160																																																																																																																																																																																										
Height tiller in driving position min./max.	h14 (mm)		796/1219																																																																																																																																																																																										
Height tiller in driving position min./max. (w/ platform)	(mm)		1066/1290																																																																																																																																																																																										
Height, lowered	h13 (mm)		85																																																																																																																																																																																										
Overall length	l1 (mm)		1692																																																																																																																																																																																										
Length to face of forks	l2 (mm)		532																																																																																																																																																																																										
Overall width	b1 (mm)		710																																																																																																																																																																																										
Fork dimensions	s • e • l (mm)		55x175x1150																																																																																																																																																																																										
Distance between fork-arms	b5 (mm)		560																																																																																																																																																																																										
Ground clearance, centre of wheelbase	m2 (mm)		28																																																																																																																																																																																										
Aisle width for pallets 1000 x 1200 sideways	Ast (mm)		1731																																																																																																																																																																																										
Aisle width for pallets 800 x 1200 lengthways	Ast (mm)		1931																																																																																																																																																																																										
Turning radius	Wa (mm)		1536																																																																																																																																																																																										
Travel speed, laden/unladen	km/h		6/6																																																																																																																																																																																										
Lift speed, laden/unladen	m/s		0.04/0.05																																																																																																																																																																																										
Lowering speed, laden/unladen	%		0.05/0.05																																																																																																																																																																																										
Max. gradeability, laden/unladen *1			8/20																																																																																																																																																																																										
Service brake			Electric																																																																																																																																																																																										
Drive motor rating S2 60 min	kW		1.2																																																																																																																																																																																										
Lift motor rating at S3 15 %	kW		1.2																																																																																																																																																																																										
Battery acc. to DIN 43531/35/36 A, B, C, no			Option																																																																																																																																																																																										
Battery voltage/nominal capacity	Ah/5hr		24V/150 (250Ah)																																																																																																																																																																																										
Battery weight	kg		151																																																																																																																																																																																										
Energy consumption acc. to VDI cycle	kWh/h		-																																																																																																																																																																																										
- Battery type			Traction battery																																																																																																																																																																																										
Type of drive unit			AC																																																																																																																																																																																										
Steering design			Mechanical																																																																																																																																																																																										
Sound pressure level at the driver's seat acc. to EN 12053	dB(A)		63																																																																																																																																																																																										
2.	Delivery cost to North Brunswick, NJ 08902	1	Each																																																																																																																																																																																										
	Total cost																																																																																																																																																																																												

\*1) At friction coefficient  $\mu=0.6$  with 1.6 km/h

## GENERAL CONDITIONS / REQUIREMENTS

1. Your quotation in English language, should be accompanied by adequate technical documentation other printed material or pertinent information (in English language) for each item quoted.
2. **The prices should include delivery cost to North Brunswick, NJ 08902 .**

## OTHER CONDITIONS

Delivery Time	10 days after notice to proceed
Payment Terms	Per Prompt Payment Act FAR Subpart 32.9 <a href="https://www.acquisition.gov/content/part-32-contract-financing">https://www.acquisition.gov/content/part-32-contract-financing</a>
Validity of Quotation	30 DAYS
Mode of Transport	AIR
	SURFACE
	SEA
	OTHERS
Contract format	Standard US Embassy Purchase order

## PLEASE STATE

<ul style="list-style-type: none"><li>• Quantity discount and early payment discount</li><li>• Separate quote for estimated transportation &amp; insurance charges</li></ul>	<ul style="list-style-type: none"><li>• Availability of local service in country of final decision</li><li>• Details on any warranty / guarantee conditions</li><li>• Delivery period</li></ul>
--	---

## SUBMISSION REQUIREMENTS

All quotations duly signed and stamped shall be submitted by electronic mail to the following address [TashkentProcurement@state.gov](mailto:TashkentProcurement@state.gov) or in sealed envelope via mail/express mail or by hand to the address below not later than **September 23, 2020 12:00 Tashkent time**

US Embassy Uzbekistan  
3, Mayqorghon Street,  
5th Block, Yunusobod District  
Tashkent, 100093  
Republic of Uzbekistan

**Late bids will be rejected**

### ATTENTION:

Please indicate on e-mail subject the RFQ reference i.e. "**RFQ/ 19UZ8020Q0022**".

Applicants with questions regarding this bidding should send them in writing (fax or E-mail) to:

US Embassy Uzbekistan  
Fax: +998 78 120 63 35  
or e-mail: [TashkentProcurement@state.gov](mailto:TashkentProcurement@state.gov)  
Attn: Procurement Department